

Sidewall film-clamp

Easy lock sidewall film over the wall



During ensiling:

- Thanks this useful stainless steel clamp, sidewall film stay on the bunker wall during the filling of the bunker.
- Film remains intact thanks to the unique rounded edges.
- Very easy to place the wall film with the clamp, standing on the silage bunker floor.
- One person is able to place the wall film over the wall of the silage bunker.
- After ensilage easy to remove from the wall.
- Long lifetime by using high quality stainless steel.

During feed-out:

- Keep Sidewall film near the wall
- No film in silage.
- Due the flat construction of the clamp for sidewall film, you can ride close near the bunker wall with a machine.

Specifications:

Distance: about 1 clip for 2 to 3 meters.
Bunker walls thickness: fitting thickness of 7 till 30 cm
Material: springy stainless steel, rounded edge
Delivery: a piece

Product number:	19.10.300	19.10.301	19.10.302	19.10.303
Length:	± 70 cm	± 120 cm	± 120 cm	± 120 cm
Walls thickness:	7 to 15 cm	7 to 15 cm	13 to 22 cm	20 to 30 cm



Very easy to place over the wall of the silage bunker.



Film clamping by spring construction. After the silage, easily to be removed from the upper side.



Useful during feed out to hold sidewall film in place.

November 2019

+31 (0)314 36 84 84

Smart guys, metal solutions